

ID LRU1002X

INDUSTRIAL UHF LONG RANGE READER

- Robust metal housing with M12 and M8 connectors
- 2 Watt Output Power
- High Receive Sensitivity
- 4 Antenna ports (internal Multiplexer)
- 6 Inputs / Outputs
- Output of RSSI values and phase angle
- Full support of new transponder chips with encryption (e. g. NXP UCODE DNA)
- Secure Key Storage (Secure Element)
- Support of LLRP
- Extended conformity for rail applications



Applications in the industrial environment

For applications in harsh industrial and railway environment FEIG's UHF Long Range Reader LRU1002 now also offers robust M12 and M8 connectors.

Applications in logistics

In logistics applications, too, there are often harsh environmental conditions. The LRU1002X is therefore the first choice for use in forklifts or conveyor systems.

INDUSTRIAL UHF LONG RANGE READER FOR VARIOUS APPLICATIONS

With a reading range of up to 12 m, 4 antenna connections and 4 circular connectors several long range applications in industrial environment can be realized.

Technical data

Dimensions (w x h x d)	260 mm x 157 mm x 68 mm
Weight	approx. 1,800 g
Housing	Aluminum, powder coated
Color	anthracite
Protection class	IP53 (IP64 with protection cap*)
Power supply	24 V DC \pm 20 %
Power consumption	max. 24 VA**
Operating frequencies	
Version EU	865 MHz up to 868 MHz
Version FCC	902 MHz up to 928 MHz
Output power	100 mW to max. 2 W configurable in steps of 100 mW
Antenna connector	4x SMA-Female (50 Ohm), integrated Multiplexer, support of external Multiplexer ID ISC.ANT.UMUX
RF-diagnosis	RF-channel monitoring, Antenna SWR control, internal overheating control
Connections	I/O M8 (8-pin), RS232 / relay M8 (8-pin), Ethernet M12, power supply M8 (4-pin)
Outputs	
2 Optocoupler	max. 24 V DC / 20 mA
2 Relays	max. 24 V DC / 1 A switching current, 2 A permanent current
Inputs	
2 Optocoupler	max. 24 V DC / 20 mA
Interfaces	RS232, Ethernet, USB (On-The-Go), Wiegand (Scan Mode Interface)
Reader modes	ISO Host Mode, Scan Mode (HID), Notification Mode, Buffered Read Mode
Supported transponders	EPC Class1 Gen2, EPC Class1 Gen2 V2, ISO 18000-6C
Indicator	16 LEDs for diagnosis of reader operation and antenna status
Others	Anti-Collision, Output of RSSI values and phase angle, Battery assisted Real Time Clock, Supports encrypted transponder communication, Secure Key Storage, "Config Cloning" function
Temperature range	
Operation	-40 °C up to +70 °C***
Storage	-25 °C up to +85 °C
Relative air humidity	5 % up to 95 % (non-condensing)
Vibration	EN 60068-2-6 10 Hz up to 150 Hz: 0.075 mm / 1 g
Shock resistance	EN 60068-2-27 Acceleration: 30 g

* Optionally a connector sealing cap is available which covers the connectors, offers a pull relief for the connected cables and guarantees enclosure rate IP64.

** Not including power consumption due to external Multiplexer

*** Tested according to EN 60068-2-1/-2-2



Connections and circular connectors of ID LRU1002X

Standard conformity

Radio license

Europe, UK	EN 302 208
USA	FCC 47 CFR Part 15
Canada	IC RSS-GEN, RSS-210
EMC	EN 301 489
Safety & Health	EN 62368-1
	EN 50364

Railway (rolling stock)

Isolation	EN 50 155
EMC	EN 50 121-3-2
EMC	EN 50 121-4
Vibration	EN 61 373 Cat 1B
Shock	EN 61 373 Cat 1B
Wet heat (cyclic)	EN 50 155 /
	EN 60 068-2-30
Fire protection	EN 45 545
Upper and lower voltage	EN 50 155
Power supply interruption	EN 50 155,
	classes S1 and C1
Power supply overvoltage	EN 50 155
Voltage fluctuation	EN 50 155
Salt mist	EN 50 155



Distributed by

SOFTWARE SrL
Via Zanardelli, 13/A
25062 Concesio (BS) Italy
Tel. +39 030 200 81 49
www.rfidglobal.it

FEIG

FEIG ELECTRONIC GmbH
35781 Weilburg, Germany, info@feig.de, www.feig.de

Information updated: November 2022. The information in this document is subject to change without prior notice and is not to be considered as a warranted characteristic. All brand names, trademarks or logos are the property of their respective owners.

INDUSTRIAL UHF LONG RANGE READER FOR VARIOUS APPLICATIONS

With a reading range of up to 12 m, 4 antenna connections and 4 circular connectors several long range applications in industrial environment can be realized.

ID LRU1002X is a powerful UHF RFID reader with 4 antenna ports. With the robust M12 (Ethernet) and M8 (power supply, I/Os and RS232) connectors the reader is designed for the harsh industrial and railway environment. Even in time critical applications multiple antennas could be used due to its internal high speed multiplexer. The reader is characterized by the following features:

- › High receiver sensitivity cares for an enlarged and at the same time homogeneous tag detection range
- › Possible secure read range of up to 12 m (40 ft) *
- › Constant high receive sensitivity and high read range also in disturbed environments and applications with a large number of readers operating at the same time
- › Support of Transponders according to EPC Class1 Gen2 and ISO 18000-6-C
- › Allows the realization of secure UHF systems by full support of new transponder chips according to EPC Class1 Gen2 V2 specification and ISO 29167 (e.g. NXP UCODE DNA)
- › Secure storage of application keys in a secure memory (Secure Element)
- › Support of EPCglobal™ Low Level Reader Protocol with special software library
- › Readout of RSSI data and phase angle of identified transponders (e.g. for localization of transponders)
- › Various configuration options for software and hardware
- › Support of 4 hardware interface ports: Ethernet, RS232, USB and Wiegand
- › Reader protection against fault conditions like antenna shortcut, antenna mismatching and electrostatic discharge
- › Robust aluminum die case housing for usage in rough and industrial environments
- › Increase of enclosure rating to IP64 due to optional available connector sealing cap for the connector block
- › Quick installation due to easy access to interfaces and antenna ports
- › 2 Inputs, 2 outputs and 2 relay outputs suit industrial needs and allow control of external components and signalization of different events
- › Antenna Port Indication: Display of active antennas (green), read events (blue) and possible antenna mismatching (red) via 4 separate LEDs

* The maximum Read Range is depending on the used antenna, the antenna cable, the used transponder and environmental conditions.

Applications



Logistics



Railway applications



Industry



Distributed by
SOFTWARE SrL
Via Zanardelli, 13/A
25062 Concesio (BS) Italy
Tel. +39 030 200 81 49
www.rfidglobal.it

FEIG

FEIG ELECTRONIC GmbH
35781 Weilburg, Germany, info@feig.de, www.feig.de

Information updated: November 2022. The information in this document is subject to change without prior notice and is not to be considered as a warranted characteristic. All brand names, trademarks or logos are the property of their respective owners.