

ID LRU1002

STANDARD UHF LONG RANGE READER

- Robust metal housing for use in industrial environment
- 2 Watt Output Power
- High Receive Sensitivity
- 4 Antenna ports (internal Multiplexer)
- 6 Inputs / Outputs
- Output of RSSI values and phase angle
- Full support of new transponder chips with encryption (e.g. NXP UCODE DNA)
- Secure Key Storage (Secure Element)
- Support of EPC Low Level Reader Protocol (LLRP) with Software Library
- Optimum price performance ratio



Logistics Applications

- › Incoming and outgoing shipments
(Gate solutions, tunnel solutions, conveyor systems)
- › Forklifts
- › E-Kanban and refill control
- › and much more

Applications Vehicle Identification

- › Vehicle Access Control
- › Tolling systems
- › Traffic management
- › Parking management
- › and much more

Other areas of application are laundries, the automotive industry, waste management and much more.

STANDARD UHF LONG RANGE READER FOR VARIOUS APPLICATIONS

With a reading range of up to 12 m and 4 antenna connections several long range applications can be realized.

Technical data

Dimensions (w x h x d)	260 mm x 157 mm x 68 mm
Weight	approx. 1,800 g
Housing	Aluminum, powder coated
Color	RAL 9003 Signal white
Protection class	IP53 (IP64 with protection cap*)
Power supply	24 V DC \pm 20 %
Power consumption	max. 24 VA**
Operating frequencies	
Version EU	865 MHz up to 868 MHz
Version FCC	902 MHz up to 928 MHz
Output power	100 mW to max. 2 W configurable in steps of 100 mW
Antenna connector	4x SMA-Female (50 Ohm), integrated Multiplexer, support of external Multiplexer ID ISC.ANT.UMUX
RF-diagnosis	RF-channel monitoring, Antenna SWR control, internal overheating control
Outputs	
2 Optocoupler	max. 24 V DC / 20 mA
2 Relays	max. 24 V DC / 1 A switching current, 2 A permanent current
Inputs	
2 Optocoupler	max. 24 V DC / 20 mA
Interfaces	RS232, Ethernet, USB (On-The-Go), Wiegand (Scan Mode Interface)
Reader modes	ISO Host Mode, Scan Mode (HID), Notification Mode, Buffered Read Mode
Supported transponders	EPC Class1 Gen2, EPC Class1 Gen2 V2, ISO 18000-6C
Indicator	16 LEDs for diagnosis of reader operation and antenna status
Others	Anti-Collision, Output of RSSI values and phase angle, Battery assisted Real Time Clock, Supports encrypted transponder communication, Secure Key Storage, "Config Cloning" function
Temperature range	
Operation	-40 °C up to +70 °C***
Storage	-25 °C up to +85 °C
Relative air humidity	5 % up to 95 % (non-condensing)
Vibration	EN 60068-2-6 10 Hz up to 150 Hz: 0.075 mm / 1 g
Shock resistance	EN 60068-2-27 Acceleration: 30 g

* Optionally a connector sealing cap is available which covers the connectors, offers a pull relief for the connected cables and guarantees enclosure rate IP64.

** Not including power consumption due to external Multiplexer

*** Tested according to EN 60068-2-1/-2-2



ID LRU1002

Standard conformity

Radio license

Europe, UK	EN 302 208
USA	FCC 47 CFR Part 15
Canada	IC RSS-GEN, RSS-210
EMC	EN 301 489
Safety & Health	EN 62368-1
	EN 50364

STANDARD UHF LONG RANGE READER FOR VARIOUS APPLICATIONS

With a reading range of up to 12 m and 4 antenna connections several long range applications can be realized.

The UHF Long Range Reader ID LRU1002 is a high performance Long Range Reader that can be used in different kind of applications. The reader convinces with an excellent price performance ratio and is characterized by the following features:

- › High receiver sensitivity cares for an enlarged and at the same time homogeneous tag detection range
- › Possible secure read range of up to 12 m (40 ft) *
- › Constant high receive sensitivity and high read range also in disturbed environments and applications with a large number of readers operating at the same time
- › Support of Transponders according to EPC Class1 Gen2 and ISO 18000-6-C
- › Allows the realization of secure UHF systems by full support of new transponder chips according to EPC Class1 Gen2 V2 specification and ISO 29167 (e.g. NXP UCODE DNA)
- › Secure storage of application keys in a secure memory (Secure Element)
- › Support of EPCglobal™ Low Level Reader Protocol with special software library
- › Readout of RSSI data and phase angle of identified transponders (e.g. for localization of transponders)
- › Various configuration options for software and hardware
- › Support of 4 hardware interface ports: Ethernet, RS232, USB and Wiegand
- › Reader protection against fault conditions like antenna shortcut, antenna mismatching and electrostatic discharge
- › Robust aluminum die case housing for usage in rough and industrial environments
- › Increase of enclosure rating to IP64 due to optional available connector sealing cap for the connector block
- › Quick installation due to easy access to interfaces and antenna ports
- › 2 Inputs, 2 outputs and 2 relay outputs suit industrial needs and allow control of external components and signalization of different events
- › Antenna Port Indication: Display of active antennas (green), read events (blue) and possible antenna mismatching (red) via 4 separate LEDs

* The maximum Read Range is depending on the used antenna, the antenna cable, the used transponder and environmental conditions.

Applications



Logistics



Vehicle Identification



Industry



Distributed by
SOFTWARE Srl
Via Zanardelli, 13/A
25062 Concesio (BS) Italy
Tel. +39 030 200 81 49
www.rfidglobal.it

FEIG

FEIG ELECTRONIC GmbH
35781 Weilburg, Germany, info@feig.de, www.feig.de

Information updated: November 2022. The information in this document is subject to change without prior notice and is not to be considered as a warranted characteristic. All brand names, trademarks or logos are the property of their respective owners.