



# C61

## Mobile Computer



Android



4G



WiFi



Bluetooth



1D Barcode



2D Barcode



NFC



UHF



Camera



GPS

Chainway C61 is a new generation rugged handheld computer with robust performance. Built with Android 9.0 OS and Qualcomm Octa-Core processor, it supports numeric/QWERTY keypad, abundant accessories like trigger handle, and features powerful removable battery. And it delivers optional barcode scanning, RFID, NFC, etc. This mobile computer can fulfill applications in logistics, warehousing, retail, etc.



# Specification

## Physical Characteristics

|                      |   |
|----------------------|---|
| <b>Dimensions</b>    | 202.0 x 72.5 x 32.0 mm / 7.95 x 2.85 x 1.26 in.   |
| <b>Weight</b>        | 370g / 13.05oz. (SE4710); 404g / 14.25oz. (SE4850)  |
| <b>Keypad</b>        | Main keyboard: 37 keys in total<br>Side keys: 2 SCAN keys + 2 volume keys + 1 user-defined key  |
| <b>Battery</b>       | 6700 mAh removable main battery, 5200 mAh optional pistol battery, support QC3.0 and RTC; Built in 100mAh backup battery, supporting battery hot swap, improving reliability and ensuring user data security<br>Standby: up to 680 hours (only main battery); WiFi: up to 560h; 4G: up to 560h<br>Continuous use: over 12 hours (depending on user environment)<br>Charging time: 3.5 hours (charge device by standard adaptor and USB cable) |
| <b>Speaker</b>       | Support   |
| <b>Vibrator</b>      | Support   |
| <b>Microphone</b>    | 2 Microphones, 1 for noise reduction  |
| <b>Display</b>       | 4-inch high definition full display, IPS LTPS 800*480   |
| <b>Touch Panel</b>   | Multi-touch panel, gloves and wet hands supported   |
| <b>Sensor</b>        | Gravity sensor, proximity sensor, light sensor, accelerometer sensor, vibration motor   |
| <b>Indicator LED</b> | Power, charging, status indicator   |
| <b>Card slot</b>     | 1 slot for SIM card, 1 slot for TF card   |
| <b>Interfaces</b>    | USB3.0, Type-C, OTG, extended thimble   |

## Performance

|                  |                                     |
|------------------|-------------------------------------|
| <b>CPU</b>       | Qualcomm 1.8 GHz Octa-core          |
| <b>RAM+ROM</b>   | 2GB+16GB / 3GB+32GB / 4GB+64GB      |
| <b>Expansion</b> | Supports up to 128 GB Micro SD card |

## Developing Environment

|                         |   |
|-------------------------|---|
| <b>Operating System</b> | Android 9.0; GMS, Android Enterprise, Zero-Touch, FOTA, Soti MobiControl, SafeUEM supported |
| <b>SDK</b>              | Chainway Software Development Kit   |
| <b>Language</b>         | Java  |
| <b>Tool</b>             | Eclipse / Android Studio  |

## User Environment

|                             |   |
|-----------------------------|---|
| <b>Operating Temp.</b>      | -20 °C to +50 °C  |
| <b>Storage Temp.</b>        | -40 °C to +70 °C  |
| <b>Humidity</b>             | 5% RH to 95% RH (non condensing)  |
| <b>Drop Specification</b>   | Multiple 1.8 m / 5.9 ft. drops (at least 20 times) to the concrete across the operating temperature range |
| <b>Tumble Specification</b> | 1000 x 0.5 m / 1.64 ft. falls at room temperature   |
| <b>Sealing</b>              | IP65 per IEC sealing specifications   |
| <b>ESD</b>                  | ±15 KV air discharge, ±8 KV conductive discharge  |

## Communication

|             |  |
|-------------|--|
| <b>WLAN</b> | Support 802.11 a/b/g/n/ac/d/e/h/i/k/r/v, 2.4G/5G dual-band, IPV4, IPV6;<br>Fast roaming: PMKID caching, 802.11r, OKC<br>Operating Channels: 2.4G(channel 1**13), 5G(channel 36,40,44,48,52,56,60,64,100,104,108,112,116,120, 124,128,132,136,140,144,149,153,157,161,165), Depends on local regulations<br>Security and Encryption: WEP, WPA/WPA2-PSK(TKIP and AES), WAPI-PSK—EAP-TTLS, EAP-TLS, PEAP-MSCHAPv2, PEAP-LTS, PEAP-GTC, etc. |
|-------------|--|

|                            |   |
|----------------------------|---|
| <b>WWAN (Europe, Asia)</b> | 2G: 850/900/1800/1900 MHz<br>3G: CDMA EVDO: BC0<br>WCDMA: 850/900/1900/2100 MHz<br>TD-SCDMA: A/F(B34/B39)<br>4G: B1/B3/B5/B7/B8/B20/B38/B39/B40/B41 |
| <b>WWAN(America)</b>       | 2G: 850/900/1800/1900MHz<br>3G: 850/900/1900/2100MHz<br>4G: B2/B4/B5/B7/B12/B17/B38   |
| <b>Vo-LTE</b>              | Support Vo-LTE HD video voice call  |
| <b>Bluetooth</b>           | Bluetooth 4.2/4.1+HS/4.0/3.0+HS/2.1+EDR   |
| <b>GNSS</b>                | GPS/AGPS, GLONASS, BeiDou, Galileo, internal antenna  |

## Data Collection

### Camera

|                    |                                 |
|--------------------|---------------------------------|
| <b>Rear Camera</b> | Rear 13 MP Autofocus with flash |
|--------------------|---------------------------------|

### NFC

|                  |   |
|------------------|---|
| <b>Frequency</b> | 13.56 MHz                                     |
| <b>Protocol</b>  | ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc. |
| <b>Chips</b>     | M1 card (S50, S70), CPU card, NFC tags, etc.  |
| <b>Range</b>     | 2-4 cm  |

### UHF (Optional)

|                           |  |
|---------------------------|--|
| <b>Engine</b>             | CM2000-1 module based on Impinj Indy R2000   |
| <b>Frequency</b>          | 865-868 MHz / 920-925 MHz / 902-928 MHz  |
| <b>Protocol</b>           | EPC C1 GEN2 / ISO18000-6C  |
| <b>Antenna</b>            | Circular Polarized Antenna (4 dBi)   |
| <b>Power</b>              | 1W (30 dBm, +5 dBm to +30 dBm adjustable)<br>2W Optional (33 dBm, for Latin America, etc.) |
| <b>R/W range</b>          | > 25 m (indoors); > 15 m (open outdoors, Impinj MR6 tag)                                   |
| <b>Fastest Read Rate</b>  | 900+ tags/sec  |
| <b>Communication Mode</b> | Pin Connector  |

\*Ranges and rates depend on tags and environment

### Barcode Scanning (optional)

|                         |   |
|-------------------------|---|
| <b>2D Scanner</b>       | Zebra: SE4710/SE4750/SE4850   |
| <b>1D Symbolologies</b> | UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.  |
| <b>2D Symbolologies</b> | PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc. |

### Optional accessories(See details in Accessory Guide)

Separate handle with one button;

Handle + battery (handle battery 5200 mAh, one button);

UHF back clip + handle (5200 mAh, one button);

Wrist Strap; Charging Cradle

Notice: Product specifications are subject to change without prior notice. / Model: C61 / Update Date: 2020-06-18



**SOFTWORK Srl**

Via Zanardelli, 13/A - 25062 Concesio (BS) Italy

Tel. +39 030 2008149 - [www.rfidglobal.it](http://www.rfidglobal.it)